

Brewmaster
SINCE • 1971

Stainless

FAUCET, KNOB & SHANK



Includes:

- 4" Stainless Shank With 1/4" Nipple, Gasket & Hex Nut
- Completely Stainless Faucet
- Plastic 2.5" Faucet Knob



Getting Started:

WARNING: Always wear protective eye wear when drilling metal.

TOOLS NEEDED: 1" hole saw and a sturdy drill.

INSTALLATION NOTE: On a fridge there are generally no coolant lines running through the door, but please check to see there are no lines connecting the door and the rest of the refrigerator. To test for coolant lines on a freezer, start with a warm freezer, then plug the unit in with the lid open. You should be able to see condensation on the inside of the freezer where lines are running. Use caution when drilling.

Installation:

- 1** Decide where you want the faucet to be on the outside of the refrigerator/cold box. Mark the spot and then drill a 1" hole using your hole saw and drill.
- 2** Take the back nut off of the threaded shank and push the shank into the hole you just drilled, so that the flange (usually black) is flush with the outside of the refrigerator. Screw the back nut onto the back of the shank, from inside the refrigerator, so that the shank is firmly secured.
- 3** Connect your dual gauge regulator to the 5 lb CO₂ tank with a crescent wrench. Do not over-tighten the regulator as you may split the built-in gasket if too much force is applied. The gauge that goes to 2000 psi is your tank gauge and tells you how much gas is left in your tank. A normal 5 lb CO₂ tank will hold from 600–1000 psi of pressure when filled, depending on the temperature the tank is stored in. The gauge that goes to 60 psi is your outgoing gauge, and tells you what amount of pressure is being released into the keg.